

RUBBERTOUGH® 360

HEAVY-DUTY SIGN POSTS & VERTICAL PANELS



OVERVIEW

The Safe-Hit **RubberTough® 360** heavy duty sign posts and vertical panels are composed of a durable two-piece omni-directional hinge and feature a large 3-1/2" post diameter.

RubberTough 360 products are composed of a durable two-piece omni-directional hinge and feature a large 3-1/2" post diameter. Having been successfully tested to withstand multiple vehicle bumper impacts and wheel-overs with large vertical panel signs attached, they are ideal for areas that need an imposing *must-be-seen* presence, yet rebound to vertical when hit. The omni-directional hinge utilizes proven Dura-Post® material technology combined with a heavy-duty inner tube to achieve the strong yet flexible design required to rebound larger, heavy posts and signage. Multiple mounting options are available including bolt-down surface mount, portable mat with quick connect pins, and quick-change soil anchors.

FEATURES AND BENEFITS

- ▶ Rebounds when impacted from any direction.
- ▶ FHWA accepted
- ▶ Superior stability & reboundability.
- ▶ Reliable galvanized steel bases and anchors have no plastic parts.
- ▶ Heavy Duty thick 3-1/2" diameter sign post.
- ▶ MUTCD compliant signage.
- ▶ Scientifically proven effective in a university study.
- ▶ Double-sided versions available to effectively warn both directions of traffic.
- ▶ Corrosion and UV resistant.
- ▶ Multiple mounting methods available.
- ▶ Easy to store. Detachable base stacks for efficient storage.
- ▶ Assembles and dismantles in seconds with quick-connect pins.
- ▶ Remains in service after multiple impacts.
- ▶ Serviceable hinge.
- ▶ Withstands extreme weather conditions.
- ▶ No sandbags required for ballast.



WWW.SAFE-HIT.COM

HEAVY DUTY DELINEATION & INDICATION



- 1 INNOVATIVE OMNI-DIRECTIONAL HINGE WITHSTANDS IMPACTS FROM ALL DIRECTIONS
- 2 MUTCD COMPLIANT SIGN PANELS
- 3 HEAVY DUTY 3-1/2" DIAMETER POST
- 4 MULTIPLE MOUNTING OPTIONS

SPECIFICATIONS

SIGN POST

Standard Color: White (other colors available)
 Post Height: 24" - 66"
 Post Diameter: 3-1/2"
 Hinge: Omni-directional polymeric material with steel attachment hardware
 Post Material: Colorfast, UV resistant thermoplastic
 Hardware: Zinc plated fasteners, stainless steel available

SIGN PANELS

Reflective: High intensity ASTM Type III, IV, IX, X
 Substrate: Flexible polyethylene
 Dimensions: Multiple sizes available

SURFACE MOUNT PERM. BASE

Material: Galvanized steel
 Hardware: Self-tapping masonry screws



QUICK-CHANGE SOIL ANCHOR

Material: Galvanized steel
 Hardware: 1/2" bolts
 Driving tools: Standard Safe-Hit driving tools



QUICK-CONNECT PORTABLE MAT

Material: Recycled crumb rubber
 Dimensions: 34" x 15" x 2-1/8"
 Weight: 38 lbs
 Hardware: Quick-connect locking pins



35 East Wacker Drive • Chicago, IL 60601
 Tel: (800) 537-8958 • Fax: (800) 770-6755
 www.quixtrans.com

Distributed By:

General specifications for RubberTough 360 products are subject to change without notice to reflect improvements and upgrades. Additional information is available in the Product Manual for this system. Contact Safe-Hit for details.